



TECHNICAL DATA SHEET

FLUXAL 1236



APPLICATION FIELD

Metallic powder for brazing of light alloys and/or manufacture of brazing paste

CHARACTERISTICS, CHEMICOPHYSICAL PROPERTIES

Metallic powder, spherical shaped grain . Composition: Alloy Al/Si 12 % +/- 1 Density: 1.1 to 1.2 Analyses: Silicon : 11 to 13 %

Magnesium : 0.050 % Manganese : 0.400 % Iron : 0.500 % Zinc : 0.100 % Copper : 0.050 % Titanium : 0.150 % Aluminium : 88+/-1% Oxygen : 0.15 %

PACKAGING

Plastic bucket 5 Kg Kraft drum of 50 Kg

MISCELLANEOUS

All active materials are in compliance with REACH. Refer to MSDS (Health and Safety data sheet) – available on demand. Note: The contents of this data sheet result from our knowledge and experience of the product. It is given as an indication but does not engage our responsibility for each particular case.

www.stts-flux.com

STTS Rue de la Distillerie / Z.A.E. La Neuvillette 60240 FLEURY – France

Tel : +33 (0)3 44 49 02 19 Fax : +33 (0)3 44 49 11 40

Mail : stts@stts-flux.com